

## Equipment

The following tables show the figures of the dimensions and capacity in metric and imperial.

The tables also provides the range of containers available:

	<b>20' Standard</b>	<b>40' Standard</b>	<b>40' High Cube</b>	<b>40' High Cube Refrigerated Container</b>	<b>20' Opentop</b>	<b>40' Opentop</b>	<b>20' Flatrack</b>	<b>40' Flatrack</b>
Size and Type Grouping Code	20GP	40GP	40HC	40RF	20OT	40OT	20FR	40FR
Dimension and Type Code	22G1	42G1	45G1	45R1	22U1	42U1	22P3	42P3
<b>External Dimensions</b>								
Length (mm) *	6,058	12,192	12,192	12,192	6,058	12,192	6,058	12,192
Width (mm) *	2,438	2,438	2,438	2,438	2,438	2,438	2,438	2,438
Height (mm) *	2,591	2,591	2,896	2,896	2,591	2,591	2,591	2,591
<b>Internal Dimensions</b>								
Length (mm) *	5,898	12,032	12,032	11,583	5,899	12,024	5,638	11,762
Width (mm) *	2,352	2,352	2,352	2,290	2,352	2,350	2,226	2,378
Height (mm) *	2,393	2,393	2,698	2,552.5	2,351	2,351	2,213	1,960
<b>Door Opening</b>								
Width (mm) *	2,340	2,340	2,340	2,294	2,340	2,338	n/a	n/a
Height (mm) *	2,280	2,280	2,585	2,574	2,280	2,279	n/a	n/a
Internal Capacity (CU. M)	33.2	67.8	76.4	67.7	32.2	67.0	n/a	n/a
Maximum Gross Mass (KG)	30,480	30,480	30,480	34,000	30,480	30,480	34,000	45,000
Average Tare (KG)	2,185	3,740	3,890	4,720	2,260	3,980	2,750	4,795
Maximum Payload (KG)	28,295	26,740	26,590	29,280	28,220	26,500	31,250	40,205

\* These specifications provide a general description of units in the fleet. Specifications may vary with manufacturer which are subject to change.

	<b>20' Standard</b>	<b>40' Standard</b>	<b>40' High Cube</b>	<b>40' High Cube Refrigerated Container</b>	<b>20' Opentop</b>	<b>40' Opentop</b>	<b>20' Flatrack</b>	<b>40' Flatrack</b>
Size and Type Grouping Code	20GP	40GP	40HC	40RF	20OT	40OT	20FR	40FR
Dimension and Type Code	22G1	42G1	45G1	45R1	22U1	42U1	22P3	42P3

**External Dimensions**

Length (feet) *	20' 0	40' 0	40' 0	40' 0	20' 0	40' 0	20' 0	40' 0
Width (feet) *	8' 0	8' 0	8' 0	8' 0	8' 0	8' 0	8' 0	8' 0
Height (feet) *	8' 6	8' 6	9' 6	9' 6	8' 6	8' 6	8' 6	8' 6

**Internal Dimensions**

Length (feet) *	19' 4	39' 6	39' 6	38' 0	19' 4	39' 5	18' 4	38' 7
Width (feet) *	7' 9	7' 9	7' 9	7' 6	7' 8	7' 8	7' 3	7' 9
Height (feet) *	7' 10	7' 10	8' 10	8' 4	7' 8	7' 8	7' 3	6' 5

**Door Opening**

Width (feet) *	7' 8	7' 8	7' 8	7' 6	7' 8	7' 8	n/a	n/a
Height (feet) *	7' 6	7' 6	8' 6	8' 5	7' 5	7' 5	n/a	n/a

Internal Capacity (CU. M)	33.2	67.8	76.4	67.7	33.2	67.0	n/a	n/a
Maximum Gross Mass (lb)	67,200 lb	67,200 lb	67,200 lb	74,800 lb	67,200 lb	67,200 lb	74,800 lb	99,207 lb
Average Tare (lb)	4,820 lb	8,245 lb	8,575 lb	10,384 lb	4,982 lb	8,774 lb	6,050 lb	10,570 lb
Maximum Payload (lb)	62,380 lb	58,955 lb	58,625 lb	64,416 lb	62,218 lb	58,426 lb	68,750 lb	88,627 lb

\* These specifications provide a general description of units in the fleet. Specifications may vary with manufacturer which are subject to change.